

# KRM33

Low-profile variable coverage speaker



## FEATURES

- Selectable horizontal coverage
- Extended frequency response
- Strong stainless steel chassis
- Controlled horizontal dispersion

## ACCESSORIES

K-R3WALL1

## COLORS AVAILABLE

BLACK



SPECIFIC RAL CODE FOR A CUSTOMIZED PAINTED MODEL



## DESCRIPTION

The KRM33 (the KRM33P is the passive model) is an ultra-compact and low-profile powered wedge speaker with a controlled horizontal pattern and an extended frequency response. It is made up of three 3.15" cone drivers and one 6" passive radiator. This combination guarantees a controlled and linear emission from 70Hz to 18KHz.

The KRM33 is equipped with a two-channel amplifier and a DSP that can be used to adjust the EQ directly inside the box. An USB direct connection guarantees an easy plug & play connection. The DSP also offers the possibility of changing the horizontal pattern of the single speaker and its bass response, two buttons located at the back of the box are used to quickly change these settings without the need of a computer.

The controlled horizontal dispersion gives the possibility of creating horizontal arrays which increase the SPL and the coverage while maintaining a high and constant signal-before-feedback within all the cluster's beams. The stainless steel chassis is a sturdy and durable box solution which is also remarkably short in height. Thanks to this feature the KRM33 can be easily and discreetly integrated in scenography designs, broadcast studios as well as under-balcony speakers in theaters.

All the components of the KRM33 are designed by the K-array R&D department and made in Italy under the K-array quality control system.

## APPLICATIONS

Broadcast/ TV Studio

Club/ DJ Set

Corporate/AV

Hospitality

House of Worship

Large Congregations

Live Concerts

Store

Theatre

Theme Park

# TECHNICAL SPECIFICATIONS

	<b>ACOUSTICS</b>		<b>AMPLIFIER</b>
Speaker power handling	180 W <sup>(AES)</sup>	Type	1 module class D - DSP controlled
Frequency range	70 Hz - 18 KHz +/- 3dB <sup>(1)</sup> / 100 Hz - 18 KHz +/- 3dB <sup>(2)</sup>	Nominal power output	2 X 125 W @ 4 Ω 1% THD + NOISE
SPL 1W/1mt	93 dB	Protection	Dynamic limiter - Over current - Short circuit
Maximum SPL	115 dB (cont.) - 121 dB (peak)	Frequency response	20 Hz - 20 KHz, all load +/- 0.5 dB
	<b>COVERAGE</b>	Damping factor 8Ω, 100 Hz	> 500
Horizontal	DSP controlled (30° / 70° selectable)	THD+N 1KHz, 1 W	0.003%
Vertical	90°		
	<b>CROSSOVER</b>	Nominal voltage	115 / 230 Vac auto switching
Type	DSP controlled	Operating range	85 - 132 Vac 170 - 264 Vac 50 - 60 Hz
Frequency	70 Hz minimum (preset dependent)	I. Nom	2 A / 115 Vac 1 A / 230 Vac
	<b>TRANSDUCERS</b>	Quiescent power (with no signal in)	10 W
	3 X 3,15" Neodymium cone driver with 1" voice coil	1/8 rated power (pink noise) @ 4 Ω	110 W
	1 X 6" passive radiator	Peak power	660 W / 120 ms
	<b>SELECTION SWITCH</b>		
Horizontal pattern	Spot - Flood	IP	40
Response	Bass Enhancer		
	<b>AUDIO INPUT</b>	<b>CERTIFICATION</b>	<b>PHYSICAL</b>
Analog connector	1 male + 1 female 3-pin balanced XLR		26.6 x 10.3 x 3.02 cm (10.47" x 4.06" x 1.189")
	<b>REMOTE CONTROL INPUT</b>	Dimensions	
Connector	1 USB type B	Weight	5.2 Kg (11.59 lbs)
	<b>POWER INPUT</b>		
Connector	2 x PowerCon IN/OUT		

<sup>(1)</sup> Maximum RMS applicable power for a musical signal. The reference signal is the one proposed by EIAJ standard  
<sup>(2)</sup> Measured with musical signal

